

Supporting communication

Floor supports for the device installation duct

Modern cable routing for glass fronts

LFS Cable routing systems



OBO
BETTERMANN

Floor supports: a popular feature in modern office buildings

Glass fronts are an optical feature of modern office buildings. This produces special requirements for supplying workstations, as there are no fixing points for the device installation duct. OBO and Ackermann can offer the ideal solution: floor supports, which you can position anywhere in the room. They allow cable routing using sheet steel and aluminium device installation ducts, thus guaranteeing connections to workstations. The floor supports are available in varying heights of between 400 mm and 900 mm. The standard colour is pure white. However, any other RAL colour can be produced: this means that, for any problem, you can find a solution which is both technical and aesthetic.



The sheet steel/aluminium unit installation duct system is fastened to the floor support using two screws, meaning that it can be installed anywhere on the floor in the room.

Type	Adjustment range	Colour	Art. no.
BOS	400–500 mm	Pure white	6288 90 0
BOS	600–700 mm	Pure white	6288 90 2
BOS	800–900 mm	Pure white	6288 90 4

Other colours are available on request.

OBO. Used by professionals.



OBO BETTERMANN GmbH & Co.
 P.O. Box 1120 · 58694 Menden, Germany
 Tel. +49 (0) 23 73 89-0 · Fax +49 (0) 23 73 89-238
 E-mail: info@obo.de · www.obo.de

Central Technical Hotline
 Tel. +49 (0) 23 73 89-1500
 Fax +49 (0) 23 73 89-1550
 E-mail: hotline@obo.de

